# Traveling Sewing Kit AGF studio

SEWYNG KIT DESYGNED BY AGF STUDIO







# FABRIC REQUIREMENTS

Fabric A C-9123 Fat Quarter Fabric B FLO-9128 Fat Quarter Fabric C FLO-9126 Fat Eighth Fabric D FLO-9129 1/3 yd. Fabric E FLO-8126 Fat Eighth Fabric F PRE-807 ⅓ yd. Fabric G PRE-811 Fat Eighth Fabric H PRE-802 Fat Eighth Fabric I DEN-L-4000 Fat Eighth



C-9123 ROADSIDE GUIDES



FLO-9129 EXPANDED AIM TERRA



PRE-811



FLO-9124 THRIVING THREADS DEEP



FLO-8126 LACE IN BLOOM CLOUD



PRE-802



FLO-9126 LACE IN BLOOM SKY



PRE-807



DEN-L-4000

# ADDITIONAL MATERIALS

- Zipper Foot #4
- Walking Foot #50 and Seam Guide
- Two (2) 9" zippers
- Fusible Fleece
- Four (4) 11" long Faux Suede Cord
- Threads: Aurifil #2312 Ermine

## **CUTTING DIRECTIONS**

- Two (2) 9" x 10 1/2" rectangles from Fabric A
- One (1) 9"x 10 1/2" rectangle from Fabric B
- One (1) 4 3/4" x 10 1/2" rectangle from Fabric B and E
- Two (2) 4 3/4" x 7 1/2" rectangles from Fabric C
- Four (4) 7" x 10 1/2" rectangles from Fabric D
- Four (4) 5" x 10 1 /2" rectangles from Fabric F
- Two (2) 1 1/4" x 3 1/2" strip from Fabric D and F
- Two (2) 3 1/2" squares from Fabric F,G, and H
- One (1) 4 1/2" x 16" strip from Fabric I
- One (1) 1" x 16" strip from Fusible Fleece
- One (1) 10 1/2" x 17 1/2" rectangle from Woven Fusible Cotton Interfacing and Fusible Fleece
- Three (3) 3" squares from Fusible Fleece



# **CONSTRUCTION**

Read through all instructions before beginning. Sew all rights sides together with 1/4" seam allowance unless stated otherwise.

#### Step 1: Sewing the Straps

- Take a 4 1/2" x 16" strip from Fabric I and iron fusible to the wrong side of the fabric on the edge of your strip.
- Next fold each side of strip into the center so raw edges meet and then fold in half and press flat.
- To make sewing easier when I am working with thicker fabrics and fusible fleece I like to use my walking foot.
- Insert the foot sideways from the right behind the needle, placing the fork up over the needle clamp and the shank under the positioning cone.
   Attach by securing the clamp lever.
- Topstitch each side of your strap at 1/4". Move needle position all the way to the left and set your stitch length to 4. Place the right inside edge of walking foot against the edge of your strap.
- Next cut strap in half and you have now created to the two loops for your sewing kit.

#### Step 2: Creating the Pin Patches

- Take two 3 1/2" squares from Fabric H and iron a 3" piece fusible fleece to one of the squares on the wrong side of the fabric. Place both squares right side together and sew all the way around your pieces at 1/4" leaving a small unsewn portion to pull right side of the fabric through.
- Pull right side of fabric through and tuck under unsewn portion and press square flat. Topstitch around your square as close to the edge as possible.
- Repeat this same process for the other 3 1/2" squares from Fabric F and G.

#### Step 3: Sewing the Pencil Pocket

- Sew two 4 3/4" x 7 1/2" rectangles from Fabric C, Press and topstitch seam at 1/2". Take a 4 3/4" x 10 1/2" rectangle from Fabric E and place pocket on top and pin in place.
- Take your 4 3/4" x 10 1/2" rectangle from Fabric B and sew pieces together.

#### Step 4: Sewing the Zipper Pockets

- Attach your zipper foot to your machine, Foot number 4.
- To be able to sew with your zipper foot push the home button. Use the arrow keys to get to the creative consultant button. Press ok.
- Select the icon for Light Weight woven fabrics and press ok.
- Use the arrow keys to select the zipper function.
  Press ok and now your machine is programed with the proper settings to sew your zipper.
- Take a 1 1/4" x 3 1/2" strip from Fabric F fold in ends to the center of your strip and then fold in half. Sandwich zipper ends inside zipper tab and sew as close to the edge as possible. Repeat this same process for the other 1 1/4" x 3 1/2" strip from Fabric F and sew to the other end of your zipper
- Take a 5" x 10 1/2" rectangle from Fabric F and place zipper facing down on the right side of the fabric. Place another 5" x 10 1/2" rectangle on top.
- Pin and stitch right up against the zipper. Open zipper half way. As your stitching right against the zipper when you get to the zipper pull with the needle in the down position lift presser foot and zip zipper shut. Now you are able to keep sewing to the end of your piece.
- Press seam allowance away from the zipper and edge stitch as close to the edge to stitch down the seam allowance. This will help to keep the lining down and out of the way of the zipper when unzipping or zipping your zipper.
- Next take a 5" x 10 1/2" rectangle from Fabric F.
  Place zipper piece on top of rectangle and then place another rectangle on top. Repeat the same process to sew the other side of your zipper.
- Next create the other zipper pocket with your other 9" zipper and piecesfrom Fabric D the same way we created the zipper pocket with Fabric F.



#### Step 5: Assembling the Sewing Kit

- Take your pencil pocket piece and a 9" x 10 1/2" rectangle from Fabric B and sew together at 1/4".
- Fuse woven fusible cotton interfacing on the back of your piece, next fuse a piece of fusible fleece.
- Sew 1/4" from each side seam.
- To create the dividers for your pencil pocket stitch about one inch width lines. Use your seam guide by lining it up with the 1" mark.
- To attach your pin patches pin them into place and stitch around each square to secure to sewing kit.
- Next take both zipper pockets and pin together. Place them at the bottom of your piece.
- Sew each side at 1/4" to secure pockets into place.
- Next take your loops and pin them 3 1/2" in from each side.
- Take your 11" long suede cording and pin them 4" down from each side.
- Stitch down loops and suede cording to secure to sewing kit.
- Sew together two 9" x 10 1/2" rectangles from Fabric A.
- Place right sides together making sure to match up seams and sew all the way around your piece at 1/2" leaving a small unsewn portion to flip piece through.
- Clip corners at seam allowance to help get nice pointy corners, flip your piece through the unsewn portion and press flat and hand-stitch unsewn portion closed.





# Congratulations







## artgalleryfabrics.com

NOTE: While all possible care has been taken to ensure the accuracy of this pattern, We are not responsible for printing errors or the way in which individual work varies.

Please read instructions carefully before starting the construction of this quilt. If desired, wash and iron your fabrics before starting to cut.

© 2016 Courtesy of Art Gallery Quilts LLC. All Rights Reserved.